

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 June 2005 (23.06.2005)

PCT

(10) International Publication Number
WO 2005/057227 A1

(51) International Patent Classification⁷: G01R 27/02,
C25B 11/00, G01R 29/08, 31/00, 33/00, 29/00

(21) International Application Number:
PCT/CA2004/002106

(22) International Filing Date:
10 December 2004 (10.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/528,720 12 December 2003 (12.12.2003) US

(71) Applicant (for all designated States except US): B.D.H.
INDUSTRIES INC. [CA/CA]; 200, Clément-Gilbert,
Saguenay, Québec, CA G7H 5B1 (CA).

(72) Inventors; and

(75) Inventors/Applicants (for US only): AUDET, Daniel
[CA/CA]; 3430, Du Muguët, Chicoutimi, Québec, CA
G7S 5W5 (CA). PARENT, Luc [CA/CA]; 1029, rue
Melançon, Chicoutimi, Québec, CA G7H 1N8 (CA).

(74) Agent: OGILVY RENAULT; Suite 1600, 1981 McGill
College Avenue, Montreal, Québec H3A 2Y3 (CA).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

[Continued on next page]

(54) Title: SYSTEM AND METHOD TO FORECAST THE ELECTRICAL CONDUCTIVITY OF ANODES FOR ALUMINUM
PRODUCTION BEFORE BAKING



(57) Abstract: The system (10) and the method are used for forecasting the electrical conductivity of an anode (12) for aluminum production before the anode (12) is baked. In the system (10), at least one receiving coil (20,22) is coupled to an electromagnetic field emitting unit (14,18). A sensing device (30) is connected to the receiving coil (20,22), the sensing device (30) outputting a signal indicative of a variation of the electromagnetic field received by the receiving coil (20,22) as the crude anode (12), or a portion thereof, passes inside the receiving coil (20,22). A value indicative of the electrical conductivity of the anode (12) is then calculated using the signal from the sensing device (30) and signals previously obtained using reference anodes (12). This way, the electrical conductivity of the anodes (12) can be forecasted before the crude anodes (12) are baked.

WO 2005/057227 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.